

R Textbook Companion for
Linear Algebra
by Jim Hefferon¹

Created by
Ajay Ragh
B.Tech.
Information Technology
APJ Abdul Kalam Technological University
Cross-Checked by
R TBC Team

June 8, 2020

¹Funded by a grant from the National Mission on Education through ICT - <http://spoken-tutorial.org/NMEICT-Intro>. This Textbook Companion and R codes written in it can be downloaded from the "Textbook Companion Project" section at the website - <https://r.fossee.in>.

Book Description

Title: Linear Algebra

Author: Jim Hefferon

Publisher: Orthogonal Publishing L3C

Edition: 3

Year: 2017

ISBN: 978-1944325039

R numbering policy used in this document and the relation to the above book.

Exa Example (Solved example)

Eqn Equation (Particular equation of the above book)

For example, Exa 3.51 means solved example 3.51 of this book. Sec 2.3 means an R code whose theory is explained in Section 2.3 of the book.

Contents

List of R Codes	4
1 Linear Systems	5
2 Vector Spaces	16
3 Maps Between Spaces	23
4 Determinants	30
5 Similarity	36

List of R Codes

Exa 2.1	solution of system of linear equations	5
Exa 1.3	Solving Linear Systems	6
Exa 2.3	solution of system of linear equations	6
Exa 3.3	system of homogeneous equations	7
Exa 1.4	Solving Linear Systems	8
Exa 2.5	finding the type of solution set of a system of linear equation	9
Exa 3.5	gauss method to reduce system of linear equations . .	9
Exa 1.7	solution of system of linear equations	10
Exa 2.7	solution of system of linear equations	11
Exa 1.8	solution of system of linear equations	12
Exa 1.9	gauss method to reduce system of linear equations . .	12
Exa 1.11	gauss method to reduce system of linear equations . .	13
Exa 1.12	gaussian elimination technique	14
Exa 2.12	vector addition	15
Exa 1.13	solution of system of linear equations	15
Exa 3.2	Linear Independence	16
Exa 3.5	Basis for the column space of the given matrix	17
Exa 1.6	Linear Independence	18
Exa 3.7	Basis for the column space of the given matrix	18
Exa 1.9	Linear Independence	19
Exa 3.9	Finding a basis for the given span	20
Exa 3.10	finding basis from reduced echelon form	20
Exa 1.16	finding the coordinates of that vector with respect to the basis	21
Exa 1.1	correspondence between vectors	23
Exa 4.1.1	Matrix Operations	23
Exa 4.1.2	Matrix Operations	24

Exa 3.1.11	Computing linear maps	24
Exa 4.2.4	Matrix Operations	25
Exa 4.2.5	Matrix Operations	25
Exa 4.2.6	Matrix Operations	25
Exa 4.3.15	Mechanics of Matrix Multiplication	26
Exa 4.4.9	Inverses	26
Exa 2.5	Computing linear maps	27
Exa 1.9	automorphism	27
Exa 2.10	Computing linear maps	28
Exa 1.11	value of h on the basis vectors	28
Exa 2.11	Computing linear maps	29
Exa 3.1	Determinants	30
Exa 1.4	Laplace Formula to find determinant	30
Exa 3.4	Determinants	31
Exa 2.5	Determinants	31
Exa 1.6	Laplace Formula to find determinant	32
Exa 2.6	Determinants	33
Exa 1.7	Laplace Formula to find determinant	34
Exa 1.10	Laplace Formula to find inverse	34
Exa 2.2	Complex Vector Spaces	36
Exa 2.2.2	Checking if matrix is diagonalizable	36
Exa 1.3	Similar Matrix	37
Exa 2.4	finding null spaces	37
Exa 3.6	Eigenvalues and Eigenvectors	38
Exa 2.10	Nilpotent matrix	38
Exa 2.17	Nilpotence index	39
Exa 2.18	nilpotence index	40
Exa 3.19	Eigenvalues and Eigenvectors	40

Chapter 1

Linear Systems

R code Exa 2.1 solution of system of linear equations

```
1 #Example 2.1 , chapter1 , section 1.2 , page 13
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib : https://github.com/friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(2,1,3,0,-1,-1,1,-1,0), ncol=3)
12 b <- c(3,1,4)
13 Ab <- cbind(A,b)
14 Ab <- rowadd(Ab,1,2,-0.5)
15 Ab <- rowadd(Ab,1,3,-1.5)
16 Ab <- rowadd(Ab,2,3,-1)
17 Ab
18 #from the result we can see that the system doesnot
   have a unique solution.
```

```
19 #We can represent the solution set by representing  
    the variables that lead(x,y) by the variable that  
    does not lead(z).  
20 #so solution set {((3/2)-(1/2)z,(1/2)-(3/2)z,z) | z  
    belongs to R}
```

R code Exa 1.3 Solving Linear Systems

```
1 #Example 1.3  
2 #Section I. Solving Linear Systems , page 3  
3 A <- matrix(c(3,-1,2,1),ncol = 2)  
4 b <- c(7,6)  
5 x <- solve(A) %*% b  
6 x
```

R code Exa 2.3 solution of system of linear equations

```
1 #Example 2.3 , chapter1 , section 1.2 , page 13  
2 #package used matlib v0.9.1  
3 #install package using command: install.packages("matlib")  
4 #Github repository of matlib : https://github.com/friendly/matlib  
5  
6 #installation and loading library  
7 #install.packages("matlib")  
8 library("matlib")  
9  
10 #program  
11 A <- matrix(c(1,0,3,0,1,1,0,-1,1,-1,6,1,-1,1,-6,-1),  
    ncol = 4)  
12 b <- c(1,-1,6,1)  
13 Ab <- cbind(A,b)
```

```

14 Ab <- rowadd(Ab,1,3,-3)
15 Ab <- rowadd(Ab,2,3,3)
16 Ab <- rowadd(Ab,2,4,1)
17 Ab
18 #from the reduced augmented matrix Ab,we can see
    that only x and y are leading ,while z and w are
    free .
19 #We represent the solution set by expressing the
    leading variables in terms of the free variables
20 #The solution set: {(2 - 2z + 2w,-1 + z - w,z,w) | z,w
    belongs to R}

```

R code Exa 3.3 system of homogeneous equations

```

1 #Example 3.3 , section 1.3 , chapter 1 ,page 24
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib :https://github.com/friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(3,2,4,-1),ncol = 2)
12 b <- c(3,1)
13 c <- c(0,0)
14 Ab <- cbind(A,b) # linear system
15 Ac <- cbind(A,c) #system of homogeneous equations
16 #reduction of original system
17 Ab <- rowadd(Ab,1,2,-2/3)
18 #reduction of homogeneous system
19 Ac <- rowadd(Ac,1,2,-2/3)

```

```
20 #comparing both
21 Ab
22 Ac
23 #Obviously the two reductions go in the same way.
24 #We can study how to reduce a linear systems by
   instead studying how to reduce the associated
   homogeneous system.
```

R code Exa 1.4 Solving Linear Systems

```
1 #Example 1.4 ,Section I. Solving Linear Systems
2 #page 3
3 #package used: matlib
4 #installation run command : install.packages("matlib")
5 #package repo : https://github.com/friendly/matlib
6
7 #installing and loading library
8 #install.packages("matlib")
9 library("matlib")
10
11 #program
12 A <- matrix(c(0,1,1/3,0,5,2,3,-2,0),ncol = 3,nrow =
   3)
13 b <- c(9,2,3)
14 Ab <- cbind(A,b)
15 Ab <- rowswap(Ab,1,3)
16 Ab <- rowmult(Ab,1,3)
17 Ab <- rowmult(Ab,1,-1)
18 Ab <- rowadd(Ab,1,2,1)
19 Ab
20 #from Ab (X3=3)( since drom row3,3*X3=9)
21 #from Ab row2 -1*X2-2*x3=-7,so X2=1
22 #from Ab row1 X1+6*x2=9,so X1 = 3
```

R code Exa 2.5 finding the type of solution set of a system of linear equation

```
1 #Example 2.5 , section 1.2 , page 15
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib : https://github.com/friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(1,2,3,2,0,2,0,1,1,0,0,-1), ncol = 4)
12 b <- c(1,2,4)
13 Ab <- cbind(A,b) #augmented matrix
14 Ab <- rowadd(Ab,1,2,-2)
15 Ab <- rowadd(Ab,1,3,-3)
16 Ab <- rowadd(Ab,2,3,-1)
17 Ab
18 #The leading variables are x, y, and w. The variable z is free.
19 #although there are infinitely many solutions , the value of w doesn't vary but is constant w = -1.
```

R code Exa 3.5 gauss method to reduce system of linear equations

```
1 #Example 3.5 , chapter 1 , section 1.3 , page 25
2 #package used matlib v0.9.1
```

```

3 #install package using command: install.packages("matlib")
4 #Github repository of matlib : https://github.com/friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(7,8,0,0,0,1,1,3,-7,-5,-3,-6,0,-2,0,-1),
12 ,ncol=4)
13 b <- c(0,0,0,0)
14 Ab <- cbind(A,b)
15 Ab <- rowadd(Ab,1,2,-8/7)
15 Ab <- rowadd(Ab,2,3,-1)
16 Ab <- rowadd(Ab,2,4,-3)
17 Ab <- rowadd(Ab,3,4,-5/2)
18 Ab

```

R code Exa 1.7 solution of system of linear equations

```

1 #Example 1.7, page nO:5
2 #package used: matlib
3 #installation run command : install.packages("matlib")
4 #package repo : https://github.com/friendly/matlib
5
6 #installing and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(1,2,1,1,-1,-2,0,3,-1),ncol = 3)
12 b <- c(0,3,3)

```

```

13 Ab <- cbind(A,b)
14 Ab <- rowadd(Ab,1,2,-2)
15 Ab <- rowadd(Ab,1,3,-1)
16 Ab <- rowadd(Ab,2,3,-1)
17 Ab
18 #from row3 : -4z=0, so z=0
19 #from row2 : -3y+3z=3, so y=-1
20 #from row1 : x+y=0, so x=1

```

R code Exa 2.7 solution of system of linear equations

```

1 #Example 2.7 , chapter one , section 1.2 , page 16
2 #package used: matlib
3 #installation run command : install.packages("matlib")
4 #package repo : https://github.com/friendly/matlib
5
6 #installing and loading library
7 install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(1,0,1,2,1,0,0,-1,2), ncol = 3)
12 b <- c(4,0,4)
13 #creating augmented matrix
14 Ab <- cbind(A,b)
15 Ab
16 #applying reduction techniques
17 Ab <- rowadd(Ab,1,3,-1)
18 Ab <- rowadd(Ab,2,3,2)
19 Ab
20 #second row: y-z=0
21 #first row: x+2*y=4
22 #so solution set is : {(4-2*z = 0)}

```

R code Exa 1.8 solution of system of linear equations

```
1 #Example 1.8 ,page 5
2 #package used: matlib
3 #installation run command : install.packages("matlib")
4 #package repo : https://github.com/friendly/matlib
5
6 #installing and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(40,-50,15,25),ncol = 2)
12 b <- c(100,50)
13 Ab <- cbind(A,b)
14 Ab <- rowadd(Ab,1,2,1.25)
15 Ab
16 #from row2 : 43.75c = 175,so c= 4
17 #from row1 : 40h+15c=100,so h=1
```

R code Exa 1.9 gauss method to reduce system of linear equations

```
1 #Example 1.9 ,chapter1 linear systems page 6
2 #Example showing gauss method to reduce given system
   of linear equations
3 #package used matlib v0.9.1
4 #install package using command: install.packages("matlib")
5 #Github repository of matlib :https://github.com/friendly/matlib
6
```

```

7 #installing and loading library
8 #install.packages("matlib")
9 library("matlib")
10
11 #program
12 A <- matrix(c(1,2,3,1,4,6,1,-3,-5), ncol = 3)
13 b <- c(9,1,0)
14 Ab <- cbind(A,b)
15 Ab <- rowadd(Ab,1,2,-2)
16 Ab <- rowadd(Ab,1,3,-3)
17 Ab <- rowadd(Ab,2,3,-(3/2))
18 Ab
19 #from Ab row3: z=3
20 #from Ab row2: y=-1
21 #from Ab row1: x=7

```

R code Exa 1.11 gauss method to reduce system of linear equations

```

1 #Example 1.11 ,page 6
2 #package used: matlib
3 #installation run command : install.packages("matlib")
4 #package repo : https://github.com/friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(1,2,0,0,-1,-2,1,0,0,1,0,2,0,2,1,1),
12   ncol=4)
13 b <- c(0,4,0,5)
14 Ab <- cbind(A,b)
15 Ab <- rowadd(Ab,1,2,-1)
16 Ab <- rowswap(Ab,2,3)

```

```
16 Ab <- rowadd(Ab,3,4,-2)
17 Ab
18 #Back-substitution gives w = 1, z = 2 , y = -1, and
   x = -1.
```

R code Exa 1.12 gaussian elimination technique

```
1 #Example 1.12 Section I. Solving Linear Systems
  page7
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib :https://github.com/
  friendly/matlib
5
6 #installing and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(1,2,2,3,1,2), ncol = 2)
12 b <- c(1,-3,-2)
13 #for this problem we cannot use normal method
  because the number of equations is more than
  number of variables
14 #so we use gaussian elimination technique.
15 gaussianElimination(A, b, tol = sqrt(.Machine$double
  .eps), verbose = FALSE,
16                      latex = FALSE, fractions = FALSE
  )
17 # result shows that one of the equations is
  redundant, here x=-2,y=1
```

R code Exa 2.12 vector addition

```
1 #Example 2.12 , section 1.2 , chapter 1 , page 18.  
2 #vector addition  
3 a <- c(2,3,1)  
4 b <- c(3,-1,4)  
5 a+b  
6 c <- c(1,4,-1,-3)  
7 7*c
```

R code Exa 1.13 solution of system of linear equations

```
1 #Example 1.13 , page 7  
2 #package used matlib v0.9.1  
3 #install package using command: install.packages("matlib")  
4 #Github repository of matlib : https://github.com/friendly/matlib  
5  
6 #installation and loading library  
7 #install.packages("matlib")  
8 library("matlib")  
9  
10 #program  
11 A <- matrix(c(1,2,2,3,1,2), ncol = 2)  
12 b <- c(1,-3,0)  
13 Ab <- cbind(A,b)  
14 Ab <- rowadd(Ab,1,2,-2)  
15 Ab <- rowadd(Ab,1,3,-2)  
16 Ab <- rowadd(Ab,2,3,-(4/5))  
17 Ab  
18 #the echelon form shows that the system is inconsistent , hence the solution set is empty
```

Chapter 2

Vector Spaces

R code Exa 3.2 Linear Independence

```
1 #Example 3.2 , Section III . Basis and Dimension , page
  127
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib :https://github.com/
  friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(2,4,3,6),ncol = 2)
12 #Rowspace(A) is this subspace of the space of two-
  component row vectors
13 #{c1.(2 3) + c2.(4 6) | c1,c2 belongs to R}
14 #simplifying A
15 A <- rowadd(A,1,2,-2)
16 A
17 #From the simplified matrix ,the second row vector is
```

linearily dependent on the first and so we can simplify the above description to
18 $\#\{c.(2 \ 3) | c \text{ belongs to } R\}$

R code Exa 3.5 Basis for the column space of the given matrix

```
1 #Example 3.5 , Section III . Basis and Dimension , page
  128
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib :https://github.com/
  friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(1,1,2,3,4,0,1,1,5),ncol = 3)
12 #From any matrix , we can produce a basis for the row
  space by
13 #performing Gauss's Method and taking the nonzero
  rows of the resulting echelon form matrix
14 #simplifying to echelon form
15 A <- rowadd(A,1,2,-1)
16 A <- rowadd(A,1,3,-2)
17 A <- rowadd(A,2,3,6)
18 A
19 #on simplification: produces the basis h(1 3 1); (0 1
  0); (0 0 3)i for the row space. This is a basis
20 #for the row space of both the starting and ending
  matrices , since the two row spaces are equal.
```

R code Exa 1.6 Linear Independence

```
1 #Chapter 2.
2 #Section II. Linear Independence
3 #Example 1.6 , page 103
4 #package used matlib v0.9.1
5 #install package using command: install.packages("matlib")
6 #Github repository of matlib : https://github.com/friendly/matlib
7
8 #installation and loading library
9 #install.packages("matlib")
10 library("matlib")
11
12 #program
13 # $c_1(40 \ 15) + c_2(-50 \ 25) = (0 \ 0)$ , check if  $\{(40 \ 15), (-50 \ 25)\}$  is linearly independent
14 A <- matrix(c(40,15,-50,25),ncol = 2)
15 b <- c(0,0)
16 Ab <- cbind(A,b)
17 Ab <- rowadd(Ab,1,2,-15/40)
18 Ab
19 #from Ab, Both c1 and c2 are zero. So the only linear relationship between the two given row vectors is the trivial relationship.
```

R code Exa 3.7 Basis for the column space of the given matrix

```
1 #Example 3.7 , Section III . Basis and Dimension , page 129
2 #package used matlib v0.9.1
```

```

3 #install package using command: install.packages("matlib")
4 #Github repository of matlib : https://github.com/friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(1,2,0,4,3,3,1,0,7,8,2,4), ncol = 3)
12 #to get a basis for the column space, temporarily
   turn the columns into rows and reduce.
13 A <- t(A)
14 A <- rowadd(A, 1, 2, -3)
15 A <- rowadd(A, 1, 3, -7)
16 A <- rowadd(A, 2, 3, -2)
17 #Now turn the rows back to columns
18 A <- t(A)
19 A
20 #The result is a basis for the column space of the
   given matrix.

```

R code Exa 1.9 Linear Independence

```

1 #Chapter 2.
2 #Section II. Linear Independence
3 #Example 1.9, page 104
4 v1 <- c(3,4,5)
5 v2 <- c(2,9,2)
6 v3 <- c(4,18,4)
7 (0*v1)+(2*v2)-1*v3
8 #the set S = {v1,v2,v3} is linearly dependent
   because this is a relationship where not all of
   the scalars are zero

```

R code Exa 3.9 Finding a basis for the given span

```
1 #Example 3.5 ,Section III . Basis and Dimension ,page  
130  
2 #package used matlib v0.9.1  
3 #install package using command: install.packages("matlib")  
4 #Github repository of matlib :https://github.com/  
friendly/matlib  
5  
6 #installation and loading library  
7 #install.packages("matlib")  
8 library("matlib")  
9  
10 #program  
11 #To get a basis for the span of {x^2 + x^4,2x^2 + 3x  
^4,-x^2 - 3x^4 } in the space row4  
12 A <- matrix(c(0,0,0,0,0,0,1,2,-1,0,0,0,1,3,-3),ncol  
= 5,nrow = 3)  
13 #applying gauss method  
14 A <- rowadd(A,1,2,-2)  
15 A <- rowadd(A,1,3,1)  
16 A <- rowadd(A,2,3,2)  
17 A  
18 #we get the basis (x^2 + x^4,x^4)
```

R code Exa 3.10 finding basis from reduced echelon form

```
1 #Example 3.10 ,Section III . Basis and Dimension ,page  
131  
2 #package used pracma
```

```

3 #install package using command: install.packages("pracma")
4
5 #installation and loading library
6 install.packages("pracma")
7 library("pracma")
8
9 #program
10 A <- matrix(c(1,2,1,3,6,3,1,3,1,6,16,6), ncol = 4,
   nrow = 3)
11 #finding row reduced echelon form ("using gauss-
   jordan reduction")
12 rref(A)
13 #Thus, for a reduced echelon form matrix we can find
   bases for the row and column spaces in
   essentially the same way, by taking the parts of
   the matrix, the rows or columns, containing the
   leading entries.

```

R code Exa 1.16 finding the coordinates of that vector with respect to the basis

```

1 #Example 1.16 ,Section III. Basis and Dimension ,page
   118
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib :https://github.com/
   friendly/matlib
5
6 #installation and loading library
7 install.packages("matlib")
8 library("matlib")
9
10 #program

```

```
11 v <- c(3,2)
12 A <- matrix(c(1,1,0,2), ncol = 2)
13 Av <- cbind(A,v)
14 Av <- echelon(A,v, reduced = TRUE)
15 Av
16 #from Av, c1 = 3 and c2 = -1=2.
```

Chapter 3

Maps Between Spaces

R code Exa 1.1 correspondence between vectors

```
1 #Example 1.1 , Section I. page 166
2 a <- c(1,2)
3 a <-t(a) #a becomes row vector
4 b <-t(a) #b becomes column vector
5 c <-c(3,4)
6 c <-t(c)
7 d <-t(c)
8 a+c
9 b+d
10 #these corresponding vectors add to corresponding
     totals
11 5*a
12 5*b
13 #correspondence respecting scalar multiplication
```

R code Exa 4.1.1 Matrix Operations

```
1 #Example1.1 , section IV:Matrix Operations , chapter3 ,
    page 224
```

```

2 #Let f : V → W be a linear function represented
   with respect to some bases by this matrix.
3 f <- matrix(c(1,1,0,1), ncol = 2)
4 #find the map that is the scalar multiple 5f: V → W
   .
5 5*f
6 #Changing from the map f to the map 5f has the
   effect on the representation of the output vector
   of multiplying each entry by 5.
7 #Therefore, going from the matrix representing f to
   the one representing 5f means multiplying all the
   matrix entries by 5.

```

R code Exa 4.1.2 Matrix Operations

```

1 #Example1.2 , section IV:Matrix Operations , chapter3 ,
   page 225
2 f <- matrix(c(1,2,3,0), ncol = 2)
3 g <- matrix(c(-2,2,-1,4), ncol = 2)
4 #two linear maps with the same domain and codomain f
   ; g: R^2 → R^2 are represented with respect to
   bases B and D by these matrices.
5 #find effect of f + g on the map
6 f+g
7 #if f does v → u and g does v → w then f + g is
   the function whose action is v → u + w.

```

R code Exa 3.1.11 Computing linear maps

```

1 #Example1.11 , section III:Computing linear maps ,
   chapter3 , page 211
2 a <- matrix(c(1,2,0,0,-1,3), ncol=3)
3 b <- c(2,-1,1)

```

```
4 a %*% b
5 #the above result can also be obtained by the method
6 x <- matrix(c(1,2),ncol = 1)
7 y <- matrix(c(0,0),ncol = 1)
8 z <- matrix(c(-1,3),ncol = 1)
9 #splitting the matrix a into component columns and
   now multiplying
10 2*x-1*y+1*z
11 #we see that both methods are equal.
```

R code Exa 4.2.4 Matrix Operations

```
1 #Example2.4 , section IV:Matrix Operations , chapter3 ,
  page 229
2 A <- matrix(c(2,4,8,0,6,2),ncol = 2)
3 B <- matrix(c(1,5,3,7),ncol = 2)
4 A %*% B
```

R code Exa 4.2.5 Matrix Operations

```
1 #Example2.5 , section IV:Matrix Operations , chapter3 ,
  page 229
2 A <- matrix(c(1,3,2,4),ncol = 2)
3 B <- matrix(c(-1,2,0,-2),ncol=2)
4 A %*% B
```

R code Exa 4.2.6 Matrix Operations

```
1 #Example2.6 , section IV:Matrix Operations , chapter3 ,
  page 230
```

```
2 A <- matrix(c(1,0,1,1,1,0),ncol=2)
3 B <- matrix(c(4,5,6,7,8,9,2,3),ncol = 4)
4 A %*% B
```

R code Exa 4.3.15 Mechanics of Matrix Multiplication

```
1 #Example3.15 , section IV.3: Mechanics of Matrix
  Multiplication , chapter3 , page 241
2 #A permutation matrix is square and is all 0's
  except for a single 1 in each row and column.
3 A <- matrix(c(0,1,0,0,0,1,1,0,0),ncol = 3) #
  permutation matrix
4 B <- matrix(c(1,4,7,2,5,8,3,6,9),ncol = 3)
5 #From the left these matrices permute rows .
6 A %*% B
7 #From the right they permute columns .
8 B %*% A
```

R code Exa 4.4.9 Inverses

```
1 #Example4.9 , section IV.4: Inverses , chapter3 , page 251
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
4 #Github repository of matlib : https://github.com/
  friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 # Augmented matrix
```

```
12 A <- matrix(c(0,1,1,3,0,-1,-1,1,0),ncol = 3)
13 B <- matrix(c(1,0,0,0,1,0,0,0,1),ncol = 3)
14 AB <- cbind(A,B)
15 echelon(A,B)
```

R code Exa 2.5 Computing linear maps

```
1 #Example2.5 , section III : Computing linear maps ,
    chapter3 , page 218
2 #package used pracma
3 #install package using command: install.packages("pracma")
4
5 #installation and loading library
6 #install.packages("pracma")
7 library("pracma")
8
9 #program
10 A <- matrix(c(1,1,0,0,2,2,0,0,2,1,3,2),ncol = 3)
11 Rank(A)
12 #Any map represented by above matrix must have three
    -dimensional domain and a four-dimensional
    codomain .
13 #Since the rank of this matrix is found to be 2 by
    above code ;
14 #Any map represented by this matrix has a two-
    dimensional range space .
```

R code Exa 1.9 automorphism

```
1 #Example 1.9 , Section I. page 170
2 #space P5 of polynomials of degree 5 or less and the
    map f that sends a polynomial p(x) to p(x - 1) .
```

```

3 #under this map  $x^2 \rightarrow (x-1)^2 = x^2 - 2x + 1$  and  $x^3 + 2x$ 
    $\rightarrow (x-1)^3 + 2(x-1) = x^3 - 3x^2 + 5x - 3$ .
4 curve( $x^2$ , from = -1000, to=1000)
5 curve(( $x-1$ ) $^2$ , from = -1000, to=1000)
6 curve( $x^3$ , from = -1000, to=1000)
7 curve(( $x-1$ ) $^3$ , from = -1000, to=1000)
8 #from these plots we can say that this map is an
   automorphism of this space.

```

R code Exa 2.10 Computing linear maps

```

1 #Example2.10 , section III : Computing linear maps ,
   chapter3 , page 219
2 #package used pracma
3 #install package using command: install.packages("pracma")
4
5 #installation and loading library
6 #install.packages("pracma")
7 library("pracma")
8
9 #program
10 A <- matrix(c(1,0,2,3), ncol = 2)
11 Rank(A)
12 #Any map from  $R^2$  to  $P_1$  represented with respect to
   any pair of bases by the above matrix;
13 #is nonsingular because this matrix has rank two.

```

R code Exa 1.11 value of h on the basis vectors

```

1 #Example 1.11 , Section II . page 186
2 #given map:  $h(1,0) = (-1,1)$  and  $h(0,1) = (-4,4)$ 
3 # $h(3,-2) = h(3*(1,0) - 2*(0,1)) = 3*h(1,0) - 2*h(0,1)$ 

```

```
4 a <- c(-1,1) # h(1,0)
5 b <- c(-4,4) # h(0,1)
6 3*a-2*b
7 #the value of h on this argument is a direct
  consequence of the value of h on the basis
  vectors.
```

R code Exa 2.11 Computing linear maps

```
1 #Example2.11 , section III: Computing linear maps ,
  chapter3 , page 220
2 A <- matrix(c(1,3,2,6), ncol=2)
3 det(A)
4 #map g: V -> W represented by above matrix is
  singular because this matrix is singular.
```

Chapter 4

Determinants

R code Exa 3.1 Determinants

```
1 #Example3.1 , chapter4 , section1 , page 329
2 X <- matrix(c(4,-2,2,6),ncol = 2)
3 #scalars come out of each row separately , not from
   the entire matrix at once .
4 #so X will become
5 A <- matrix(c(2,-1,1,3),ncol = 2)
6 #with scalars 2 & 2 coming out of rows 1 and 2
   respectively
7 c <- det(X)
8 d <- 4*det(A)
9 all.equal(c,d)
```

R code Exa 1.4 Laplace Formula to find determinant

```
1 #Example 1.4 , chapter 4 , Section III . Laplace 's
   Formula , page 354
2 #package used matlib v0.9.1 and pracma
3 #Github repository of matlib : https://github.com/
   friendly/matlib
```

```
4
5 #installation and loading library
6 #install.packages("matlib")
7 library("matlib")
8
9 #program
10 T <- matrix(c(1,4,7,2,5,8,3,6,9), ncol = 3)
11 T12 <- cofactor(T,1,2)
12 T22 <- cofactor(T,2,2)
13 T12
14 T22
```

R code Exa 3.4 Determinants

```
1 #Example3.4 , chapter 4 , page 330
2 A <- matrix(c(2,4,1,3), ncol = 2)
3 #using multilinearity property to break up the
   matrix
4 a <- matrix(c(2,4,0,0), ncol = 2)
5 b <- matrix(c(2,0,0,3), ncol = 2)
6 c <- matrix(c(0,4,1,0), ncol = 2)
7 d <- matrix(c(0,0,1,3), ncol = 2)
8 #verifying the property
9 x <- det(A)
10 y <- det(a)+det(b)+det(c)+det(d)
11 all.equal(x,y)
```

R code Exa 2.5 Determinants

```
1 #Example 2.5 , chapter4 , Section I. Definition , page 325
2 #package used matlib v0.9.1
3 #install package using command: install.packages("matlib")
```

```

4 #Github repository of matlib :https://github.com/
   friendly/matlib
5
6 #installation and loading library
7 #install.packages("matlib")
8 library("matlib")
9
10 #program
11 A <- matrix(c(2,4,0,2,4,-3,6,3,5),ncol=3)
12 b <- det(A)
13 #determinant by normal ,ethod
14 A <- rowadd(A,1,2,-2)
15 A <- rowswap(A,2,3)
16 A
17 #reducing with gaussian reduction now multiplying
   the diagonal terms,keeping in mind the sign
   change due to row swap to find determinant.
18 c <- -1*A[1,1]*A[2,2]*A[3,3]
19 all.equal(b,c)
20 #so the determinant by both techniques are the same

```

R code Exa 1.6 Laplace Formula to find determinant

```

1 #Example 1.6, chapter 4, Section III. Laplace 's
   Formula ,page 355\
2 #package used matlib v0.9.1 and pracma
3 #Github repository of matlib :https://github.com/
   friendly/matlib
4
5 #installation and loading library
6 #install.packages("matlib")
7 library("matlib")
8
9 #program
10 t <- matrix(c(1,4,7,2,5,8,3,6,9),ncol = 3)

```

```

11 x <- det(t)
12 #computing the determinant by expanding along the
   first row,
13 y <- t[1,1]*cofactor(t,1,1)+t[1,2]*cofactor(t,1,2)+t
   [1,3]*cofactor(t,1,3)
14 #computing the determinant by expanding along the
   second row,
15 z <- t[2,1]*cofactor(t,2,1)+t[2,2]*cofactor(t,2,2)+t
   [2,3]*cofactor(t,2,3)
16 all.equal(x,y)
17 all.equal(x,z)

```

R code Exa 2.6 Determinants

```

1 #Example 2.6 , chapter4 , Section I. Definition , page 326
2 #package used matlib v0.9.1 and pracma
3 #Github repository of matlib :https://github.com/
   friendly/matlib
4
5 #installation and loading library
6 install.packages("matlib")
7 library("matlib")
8
9 #program
10 A <- matrix(c(1,0,0,0,0,1,0,1,1,1,0,0,3,4,5,1), ncol
   = 4)
11 A <- rowadd(A,2,4,-1)
12 A <- rowswap(A,3,4)
13 A
14 #multiplying diagonal terms and multiplying it with
   -1 to compensate for rowswap
15 -1*A[1,1]*A[2,2]*A[3,3]*A[4,4]

```

R code Exa 1.7 Laplace Formula to find determinant

```
1 #Example 1.7 , chapter 4 , Section III . Laplace 's
  Formula , page 355
2 #package used matlib v0.9.1 and pracma
3 #Github repository of matlib : https://github.com/
  friendly /matlib
4
5 #installation and loading library
6 #install.packages("matlib")
7 library("matlib")
8
9 #program
10 t <- matrix(c(1,2,3,5,1,-1,0,1,0), ncol = 3)
11 #computing the determinant by expanding along the
  third column .
12 y <- t[1,3]*cofactor(t,1,3)+t[2,3]*cofactor(t,2,3)+t
  [3,3]*cofactor(t,3,3)
13 y
```

R code Exa 1.10 Laplace Formula to find inverse

```
1 #Example 1.10 , chapter 4 , Section III . Laplace 's
  Formula , page 356
2 #package used matlib v0.9.1 and pracma
3 #Github repository of matlib : https://github.com/
  friendly /matlib
4
5 #installation and loading library
6 #install.packages("matlib")
7 library("matlib")
8
9 #program
10 t <- matrix(c(1,2,1,0,1,0,4,-1,1), ncol = 3)
11 #finding inverse: if T has an inverse , if |T| != 0 ,
```

```
      then  $T^{-1} = (1/|T|) \text{adj}(T)$ 
12 a <- adjoint(t)
13 b <- 1/det(t)
14 i <- b*a
15 i
```

Chapter 5

Similarity

R code Exa 2.2 Complex Vector Spaces

```
1 #Example 2.2 , chapter 5 , Section I . Complex Vector  
  Spaces , page 387  
2 a <- complex(real = 1,imaginary = 1)  
3 b <- complex(real = 0,imaginary = 1)  
4 c <- complex(real = 2,imaginary = -0)  
5 d <- complex(real = -2,imaginary = 3)  
6 e <- complex(real = 1,imaginary = 0)  
7 f <- complex(real = 0,imaginary = 3)  
8 g <- complex(real = 1,imaginary = -0)  
9 h <- complex(real = 0,imaginary = -1)  
10 A <- matrix(c(a,b,c,d),ncol = 2)  
11 B <- matrix(c(e,f,g,h),ncol = 2)  
12 A %*% B
```

R code Exa 2.2.2 Checking if matrix is diagonalizable

```
1 #Example 2.2 , chapter 5 , section II .2  
  Diagonalizability , page 393
```

```
2 #matrix: T is diagonalizable if there is a  
    nonsingular P such that PTP-1 is diagonal.  
3 T <- matrix(c(4,1,-2,1),ncol = 2)  
4 P <- matrix(c(-1,1,2,-1),ncol = 2)  
5 #checking whether diagonalizable  
6 P %*% T %*% inverse(P) # diagonal matrix  
7 # so matrix P is diagonalizable
```

R code Exa 1.3 Similar Matrix

```
1 #Example 1.3 , chapter 5 , Section II . Similarity , page  
    390  
2 #package used matlib v0.9.1  
3 #Github repository of matlib : https://github.com/  
    friendly/matlib  
4  
5 #installation and loading library  
6 #install.packages("matlib")  
7 library("matlib")  
8 P <- matrix(c(2,1,1,1),ncol = 2)  
9 T <- matrix(c(2,1,-3,-1),ncol = 2)  
10 #finding similar matrix of T  
11 T1 <- P %*% T %*% inverse(P)  
12 T1
```

R code Exa 2.4 finding null spaces

```
1 #Example 2.4 , chapter 5 , section IV.2 , page 432  
2 #package used pracma v1.9.9  
3 #installing and loading library  
4 #install.packages("pracma")  
5 library("pracma")  
6 T <- matrix(c(2,1,-1,4),ncol=2)
```

```

7 a <- eigen(T)
8 a$values
9 #so T has only the single eigenvalue 3.
10 I <- matrix(c(1,0,0,1),ncol = 2)
11 T-(3*I)
12 # so for this ,the only eigenvalue is 0 and T -3I is
   nilpotent .
13 #to ease this computation we find nulspaces
14 x <- nullspace(T)
15 x

```

R code Exa 3.6 Eigenvalues and Eigenvectors

```

1 #Example3.6 ,chapter 5,section II.3 Eigenvalues and
  Eigenvectors ,page 398
2 T <- matrix(c(2,0,0,0),ncol = 2)
3 a <-eigen(T)
4 a$values
5 a$vectors

```

R code Exa 2.10 Nilpotent matrix

```

1 #Example 2.10 ,chapter 5,scetion III.2 ,page 414
2 #package used matlib v0.9.1
3 #Github repository of matlib :https://github.com/friendly/matlib
4
5 #installation and loading library
6 #install.packages("matlib")
7 library("matlib")
8 N <- matrix(c(0,1,0,0,0,0,1,0,0,0,0,1,0,0,0,0),ncol
   =4)

```

```

9 P <- matrix(c(1,0,1,0,0,2,1,0,1,1,1,0,0,0,0,1), ncol
= 4)
10 A <- P %*% N %*% inverse(P)
11 A
12 #The new matrix ,A is nilpotent; its fourth power is
the zero matrix.
13 x <- P %*% N^4 %*% inverse(P)
14 #since (PNP^-1)^4 = P * N^4 * P^-1
15 y <- det(x)
16 all.equal(y,0)

```

R code Exa 2.17 Nilpotence index

```

1 #Example 2.17 , chapter 5 , scetion III .2 , page 419
2 #package used matlib v0.9.1
3 #Github reposiory of matlib :https://github.com/friendly/matlib
4
5 #installation and loading library
6 install.packages("matlib")
7 library("matlib")
8 M <- matrix(c(1,1,-1,-1), ncol = 2)
9 #finding nilpotent index
10 A <- matrix(c(0,0,0,0), ncol = 2)
11 count <- 1
12 Y <- M
13 repeat{
14   Y <- Y %*% M
15   if (all.equal(Y,A)){
16     print(count+1)
17     break()
18   }
19   count= count+1
20 }

```

R code Exa 2.18 nilpotence index

```
1 #Example 2.18 ,chapter 5, scetion III.2 ,page 420
2 #package used matlib v0.9.1
3 #Github repository of matlib :https://github.com/friendly/matlib
4
5 #installation and loading library
6 #install.packages("matlib")
7 library("matlib")
8 M <- matrix(c
9   (0,1,-1,0,1,0,0,1,1,0,0,0,1,0,-1,0,0,-1,0,1,0,0,1,0,-1)
10  ,ncol = 5)
11 #finding nilpotent index
12 A <- matrix(c(0),ncol = 5,nrow = 5)
13 count <- 1
14 Y <- M
15 repeat{
16   Y <- Y %*% M
17   if (all.equal(Y,A)== TRUE){
18     print(count+1)
19     break()
20   }
21   count=count+1
22 }
```

R code Exa 3.19 Eigenvalues and Eigenvectors

```
1 #Example3.19 ,chapter 5, section II.3 Eigenvalues and
2 #Eigenvectors ,page 404
3 T <- matrix(c(2,0,-4,-2,1,8,2,1,3),ncol = 3)
4 a <- eigen(T)
```

4 a\$**values**
